



6 Ton PTO Spreader

Fertilizer Spreader - PTO Driven

Home of Worldwide Quality Blending, Conveying, Tending, & Spreading Products!



304 Stainless Steel Hopper

Bolt on Hopper Design


Adjustable Material Divider



Heavy Duty Rectangular Steel Tubing Frame, with Heavy Duty Corner Braces

Hydraulically Operated

8" Wide SS Mesh Conveyor Chain



Doyle Equipment Mfg. Co., Inc.

4001 Broadway, P.O. Box 3024, Quincy, IL 62305

Toll Free: 800-788-8085 Fax: 217-223-3655

E-mail: doyle@doylemfg.com Web Site: www.doylemfg.com



Standard Features:

- 14 ga. 304 stainless steel hopper construction
- 2" x 6" mild steel tubing frame, with heavy duty mild steel corner braces
- Bolt on hopper to frame, allows easy hopper removal from frame
- Heavy duty adjustable hitch
- Heavy duty 12,000 lb. tongue jack
- Tandem 8,000 lb. axles, with 8-bolt hubs
- 14 L x 16.1 implement rib tires
- 1" x 1" mesh type heavy duty 8" conveyor chain
- All metal press wheel with hydraulic engagement
- Hydraulically driven twin "dished" spinners, 20-5/16" diameter with 4 blades per spinner, specially designed for extremely accurate broadcasting of spreader
- 31.5 gallon hydraulic tank with temperature gauge, site glass, and large hydraulic filters, metal shot blasted and powder coated bright blue
- Hydraulic PTO pump, lines, hoses, and fittings
- Inspection window in hopper front
- Factory assembled & tested



Optional Features:

- Manual press wheel engagement
- Fitted nylon tarp with grommets
- Roll Tarp
- Serge brake system, one axle

Capacity
Hopper Capacity (water level)....204 cu.ft.
Hopper Side Slope..... 34 degrees

